

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
9 June 2005 (09.06.2005)

PCT

(10) International Publication Number
WO 2005/052637 A1

(51) International Patent Classification⁷: **G01T 1/29**, 1/202

(21) International Application Number:

PCT/IB2004/052447

(22) International Filing Date:

16 November 2004 (16.11.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

03104352.4 25 November 2003 (25.11.2003) EP

(71) Applicant (for DE only): **PHILIPS INTELLECTUAL PROPERTY & STANDARDS GMBH** [DE/DE]; Stein-
damm 94, 20099 Hamburg (DE).

(71) Applicant (for AE, AG, AL, AM, AT, AU, AZ, BA, BB, BE, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CY, CZ, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, SZ, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW only): **KONINKLIJKE PHILIPS ELECTRONICS N. V.** [NL/NL]; Groenewoud-
seweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **FIEDLER , Klaus** [DE/DE]; c/o Philips Intellectual Property &, Standards GmbH Weissshausstr. 2, 52066 Aachen (DE). **SOLF , Torsten** [DE/DE]; c/o Philips Intellectual Property &, Standards GmbH Weissshausstr. 2, 52066 Aachen (DE). **THON , Andreas** [DE/DE]; c/o Philips Intellectual Property &, Standards GmbH Weissshausstr. 2, 52066 Aachen (DE).


(74) Agents: **VOLMER, Georg** et al.; Philips Intellectual Property &, Standards GmbH Weissshausstr. 2, 52066 Aachen (DE).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: SCINTILLATION LAYER FOR A PET-DETECTOR



(57) Abstract: The invention relates to a scintillation layer (20) for a PET-detector. The scintillation layer (20) consists of a plurality of scintillation elements (21) that are joined together in a practically gapless way and that are oriented towards the centre of curvature (24). Depending on the form of the scintillation layer (20), the scintillation elements (21) may have for example the form of a truncated wedge or pyramid.

WO 2005/052637 A1



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Scintillation layer for a PET-detector

5 The invention relates to a scintillation layer for a PET-detector, a PET-detector with such a scintillation layer, and a procedure for the production of such a scintillation layer.

10 Scintillation layers are needed for PET-detectors in order to convert gamma-quanta into visible light. The visible light can then be detected by further sensors like for example photomultipliers. Scintillation layers often consist of a plurality of scintillation elements in the form of cuboids which are arranged side by side in the scintillation layer. Furthermore scintillation layers are often curved. Therefore, if
15 cuboid-shaped scintillation elements are assembled with their axes oriented towards the centre of curvature of the scintillation layer, tapered gaps arise at their radially external side. From the US 6 285 028 B1 a curved scintillation layer is known with cuboid-shaped scintillation elements disposed parallel to each other. By arranging the scintillation elements in different heights, a curved scintillation layer with a stepped
20 outer surface and inner surface can be made. Gamma rays which come e.g. from the centre of curvature of the scintillation layer pass the scintillation elements depending on their direction of propagation under different angles. This can lead to position dependent artifacts during the conversion of the gamma rays in the scintillation layer.

25

Based on this situation it was an object of the present invention to provide means for an improved detection of gamma rays in a scintillation layer.

 This task is solved by a scintillation layer according to claim 1, by a PET-detector according to claim 4, and by a procedure according to claim 6. Preferred
30 embodiments are subject to the dependent claims.

The scintillation layer according to the invention is in particular suited for the use in a PET-detector. It comprises a curved internal surface and/or a curved outer surface. Preferably the internal surface and the outer surface are concentric, i.e. run parallel to each other and have the same centre of curvature. Furthermore the
5 scintillation layer consists of a plurality of scintillation elements, the scintillation elements being joined together with minimal gaps between them and oriented (with their body axes and/or their side faces) towards the centre of curvature of the scintillation layer. If there are gaps greater than zero between the scintillation elements, they are typically filled by materials that are necessary for the optimal function of the
10 scintillation layer. One important example for such a material are reflecting foils which reflect light back into a scintillation element in order to avoid cross talk.

Due to the dense, practically gapless (i.e. no gaps besides the spaces needed for reflecting foils or the like) coupling of the scintillation elements the average path length a gamma ray travels in the scintillation layer becomes maximal. Therefore
15 the probability of detection for gamma-quanta and the light yield are maximal, too. Furthermore gamma rays coming from the centre of curvature run approximately parallel to the body axes of the scintillation elements at all positions of the scintillation layer and independently of their direction of propagation. Thus the gamma rays encounter homogeneous geometrical conditions everywhere in the scintillation layer so
20 that no position dependent artifacts like those in a detector according to US 6 285 028 B1 arise.

The scintillation layer may in particular be cylindrically with the scintillation elements having the form of a wedge or a frustum of a wedge, respectively.

Alternatively the scintillation layer can be curved in an ellipsoidal way.
25 In particular it can be spherically curved, i.e. have the form of a calotte. In this case the scintillation elements have the form of a frustum of a pyramid.

The invention comprises also a PET-detector with a scintillation layer that is constituted in one of the ways described above. Therefore, reference is made to the preceding description for more information on the details, advantages and
30 improvements of that PET-detector.

Finally the invention relates to a procedure for the production of a scintillation layer for a PET-detector. According to the procedure a plurality of

scintillation elements are joined together with minimal gaps between them, the gaps being typically filled with an intermediate material like a reflecting foil. The scintillation elements are shaped in such a way that the resulting scintillation layer is curved and that the body axes of the scintillation elements are oriented towards the centre of curvature of the scintillation layer when the scintillation elements are at their place in the scintillation layer.

By the procedure a scintillation layer of the kind described above is produced. Therefore, reference is made to the corresponding description for more information on the details, advantages and improvements of the procedure.

According to a preferred embodiment of the procedure the scintillation elements are cut out of larger scintillation crystals. Thus it is particularly possible to produce scintillation elements with flat surfaces.

According to an alternative method the scintillation elements are produced from ceramic scintillation materials by press-forming. The press-forming allows to produce scintillation elements with curved outer surfaces if desired.

In the following the invention is described by way of example with the help of the accompanying drawings in which:

Fig. 1 is a perspective view of a part of a scintillation layer with wedge like scintillation elements;
Fig. 2 is a perspective view of a part of a scintillation layer with pyramid-shaped scintillation elements;
Fig. 3 is a sectional view of a curved scintillation layer with differently shaped scintillation elements.

In figure 1 only a small part of a scintillation layer 10 is represented. The scintillation layer 10 is used for the conversion of γ -quanta into photons of visible light, and it can particularly be employed in a PET-detector. In this case the area of the scintillation layer is typically (semi-)annular and measures about 20 cm \times 300 cm. Moreover, at least two such scintillation layers 10 are arranged opposite to each other in

a PET-detector in order to allow detection of the coincidence of two γ -quanta from an annihilation process.

The scintillation layer 10 represented in figure 1 is bent cylindrically, the centre of curvature being an axis 14. The scintillation layer 10 is composed of a plurality of individual scintillation elements 11. In order to avoid or minimise gaps between the joined scintillation elements 11, they are shaped like frustum wedges (i.e. prisms with a trapezoidal cross section). Between two neighbouring scintillation elements 11 there is normally a reflecting foil (not shown) which fills any remaining gap. The (imaginary) tips of the corresponding whole wedges all lie on the curvature axis 14. Thus it is achieved that the scintillation elements 11 are oriented with their body axes and/or their side faces 15 towards the centre of curvature 14 of the scintillation layer 10. Since the gamma rays basically all come from an area near the centre of curvature 14 during the use of the scintillation layer 10 in a PET-detector, they hit the scintillation elements 11 parallel to their body axes. This rotational symmetry of the arrangement helps to avoid artifacts which may arise in systems like that of US 6 285 028 B1. Furthermore the probability to detect a gamma quantum in the scintillation layer 10 and the light yield a gamma quantum produces are both maximized by the minimally spaced joining of the scintillation elements 11.

The scintillation elements 11 can for example be produced by cutting them from a larger scintillation crystal. Suitable scintillation materials are particularly GSO, LYSO and LaBr₃. Since cutting basically produces flat surfaces, the internal surface 12 as well as the outer surface 13 of the scintillation layer 10 are not bent smoothly but put together from individual flat faces.

Figure 2 shows a part of another scintillation layer 20 which is spherically curved. In this case the centre of curvature is a (mid)point 24. The scintillation layer 20 again consists of a plurality of scintillation elements 21 of the same kind. In this case the scintillation elements 21 each have the form of a truncated pyramid (with rectangular and/or quadratic cross-sectional area). They are arranged in such a way that the (imaginary) tip of the pyramids reside in the centre of curvature 24. Again a maximal probability for detection of gamma rays and a high light yield as well as an isotropy with respect to the centre of curvature 24 are achieved by the practically

gapless joining of the scintillation elements 21 and by their orientation towards the centre of curvature 24.

In figure 2 the internal surface 22 as well as the outer surface 23 of the scintillation layer 20 are spherically curved in a smooth way. In order to achieve this,
5 the internal faces and outer faces of the individual scintillation elements 21 must be curved, too. Such scintillation elements 21 may be produced for example by press-forming of ceramic scintillation materials. A suitable scintillation material for this purpose is for example LuAG.

Figure 3 shows a section through a part of a scintillation layer 30 which
10 is curved in space spherically, cylindrically or otherwise. In this case the scintillation layer 30 is assembled from cuboid-shaped scintillation elements 31a which are oriented with their body axes towards the centre of curvature 34 of the scintillation layer 30. Moreover, the tapered gaps arising between the elements 31a are filled with wedge-shaped scintillation elements 31b. These tapered scintillation elements 31b are oriented
15 with their body axes towards the centre of curvature 34, too. They provide for a practically gapless scintillation layer 30 with maximum probability of detection of gamma-quanta and light yield.

CLAIMS:

1. Scintillation layer (10, 20, 30) for a PET-detector with a curved internal surface (12, 22) and/or a curved outer surface (13, 23), comprising a plurality of scintillation elements (11, 21, 31a, 31b) that are joined together with minimal gaps and that are oriented towards the centre of curvature (14, 24, 34) of the scintillation layer.
- 5 2. Scintillation layer (10) according to claim 1, characterized in that it is cylindrically curved and that it comprises scintillation elements (11) having the form of a truncated wedge.
- 10 3. Scintillation layer (20) according to claim 1, characterized in that it is curved in an ellipsoidal way and that it comprises scintillation elements (21) having the form of a truncated pyramid.
4. Scintillation layer (10, 20, 30) according to claim 1, characterized in that
15 gaps between neighbouring scintillation elements (11, 21, 31) are filled with a reflecting material.
5. PET-detector with a scintillation layer (10, 20, 30), the scintillation layer having a curved internal surface (12, 22) and/or a curved outer surface (13, 23)
20 and comprising a plurality of scintillation elements (11, 21, 31a, 31b) that are joined together with minimal gaps and that are oriented towards the centre of curvature (14, 24, 34) of the scintillation layer.
6. PET-detector according to claim 5, characterized in that the scintillation
25 layer (10, 20, 30) is designed according to one of claims 2 to 4.

7. Procedure for the production of a scintillation layer (10, 20, 30) for a PET-detector by joining a plurality of scintillation elements (11, 21, 31a, 31b) with minimal gaps, the scintillation elements being shaped in such a way that the resulting scintillation layer (10, 20, 30) is curved and that the scintillation elements (11, 21, 31a, 31b) are oriented towards the centre of curvature (14, 24, 34) of the scintillation layer.

8. Procedure according to claim 7, characterized in that the resulting scintillation layer (10, 20, 30) is designed according to one of claims 2 to 4.

9. Procedure according to claim 7, characterized in that the scintillation elements (11, 31a, 31b) are cut from scintillation crystals.

10. Procedure according to claim 7, characterized in that the scintillation elements (21) are produced by press-forming of ceramic scintillation materials.




FIG.1




FIG.2




FIG.3

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 G01T1/29 G01T1/202

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G01T

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 291 228 A (THOMPSON CHRISTOPHER J) 22 September 1981 (1981-09-22) the whole document	1-10
X	WO 03/081280 A (LI HONGDI ; URIBE JORGE (US); BAGHAEI HOSSAIN (US); UNIV TEXAS (US); W) 2 October 2003 (2003-10-02) page 3, line 20 - page 4, line 26 page 7, line 2 - page 18, line 25	1,5,7,9
X	US 2002/110216 A1 (SAITO YASUO ET AL) 15 August 2002 (2002-08-15) page 1, paragraph 13 - paragraph 15 page 2, paragraph 55 - page 4, paragraph 76 figures 7-9	1,4



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *G* document member of the same patent family

Date of the actual completion of the international search

21 January 2005

Date of mailing of the international search report

01/02/2005

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Coda, R

INTERNATIONAL SEARCH REPORT

PCT/IB2004/052447

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
US 4291228	A	22-09-1981	CA	1120616 A1	23-03-1982
			DE	3007816 A1	22-01-1981
			FR	2459488 A1	09-01-1981
			GB	2051111 A	14-01-1981
			JP	56006175 A	22-01-1981
			SE	436467 B	17-12-1984
			SE	8000773 A	20-12-1980

WO 03081280	A	02-10-2003	CA	2474761 A1	02-10-2003
			EP	1478945 A2	24-11-2004
			WO	03081280 A2	02-10-2003
			US	2003226972 A1	11-12-2003

US 2002110216	A1	15-08-2002	JP	2001242253 A	07-09-2001
			US	6396898 B1	28-05-2002